

eGaN FETs and ICs, Development Boards, Demonstration Boards and Evaluation Kits



eGaN FETs and ICs

Part Number	Configuration	V _{DS} max	V _{GS} max	Max R _{DS(on)} (mΩ) @ 5V _{GS}	Q _G typ (nC)	Q _{GS} typ (nC)	Q _{GD} typ (nC)	Q _{OSS} typ (nC)	Q _{RR} (nC)	C _{ISS} (pF)	C _{OSS} (pF)	C _{RSS} (pF)	I _D (A)	Pulsed I _D (A)	Max T _J (°C)	Package (mm)	Development Board
EPC2040	Single	15	6	30	0.745	0.23	0.14	0.42	0	86	67	20	3.4	28	150	BGA 0.85 x 1.2	n/a
EPC2111	Half Bridge	30	6	19 8	1.7 4.4	0.7 1.5	0.3 0.8	3.1 9.1	0	490 190	460 160	21 8	16	50 140	150	BGA 3.5 x 1.5	EPC9086
EPC2100	Half Bridge	30	6	8 2	3.5 15	1.4 4.6	0.57 2.6	5.5 28	0	1700 380	1600 290	110 20	9.5 38	100 400	150	BGA 6.05 x 2.3	EPC9036
EPC2023	Single	30	6	1.45	19	5.7	3.2	30	0	2150	1530	100	90	590	150	LGA 6.05 x 2.3	EPC9031
EPC8004	Single	40	6	110	0.37	0.12	0.047	0.63	0	45	23	0.8	2.7	7.5	150	LGA 2.05 x 0.85	EPC9024
EPC2014C	Single	40	6	16	2	0.7	0.3	4	0	220	150	6.5	10	60	150	LGA 1.7 x 1.1	EPC9005C
EPC2015C	Single	40	6	4	8.7	2.7	1.2	19	0	980	710	18	53	235	150	LGA 4.1 x 1.6	EPC9001C
EPC2030	Single	40	6	2.4	17	5.8	3.4	32	0	1960	1120	62	48	490	150	BGA 4.6 x 2.6	EPC9060
EPC2024	Single	40	6	1.5	18	5.1	2.4	45	0	1920	1620	29	90	560	150	LGA 6.05 x 2.3	EPC9032
EPC2108	Dual with Sync Boot	60	6	240 3300	0.24 0.044	0.106 0.02	0.047 0.004	0.71 0.93 0.134	0	22 7	13 23 1.6	0.4 0.02	1.7 0.5	5.5 0.5	150	BGA 1.35 x 1.35	EPC9059
EPC2035	Single	60	6	45	0.88	0.25	0.16	2.6	0	95	60	2	1	24	150	BGA 0.9 x 0.9	EPC9049
EPC2102	Half Bridge	60	6	4.4	6.8	2.3	1.4	23 31	0	830	710 510	14	23	215	150	BGA 6.05 x 2.3	EPC9038
EPC2031	Single	60	6	3	16	5	3	48	0	1640	980	35	48	450	150	BGA 4.6 x 2.6	EPC9061
EPC2101	Half Bridge	60	6	11.5 2.7	2.7 12	1 3.7	0.5 2.5	9 45	0	300 1200	200 1000	5 25	9.5 38	80 350	150	BGA 6.05 x 2.3	EPC9037
EPC2020	Single	60	6	2.2	16	3.9	2.3	50	0	1780	1020	24	90	470	150	LGA 6.05 x 2.3	EPC9033
EPC8002	Single	65	6	480	0.133	0.057	0.015	0.344	0	20	6.7	0.12	2	2	150	LGA 2.05 x 0.85	EPC9022
EPC8009	Single	65	6	130	0.37	0.12	0.055	0.94	0	45	19	0.5	2.7	7.5	150	LGA 2.05 x 0.85	EPC9029
EPC2039	Single	80	6	25	1.91	0.76	0.42	7.64	0	210	115	2	6.8	50	150	BGA 1.35 x 1.35	EPC9057
EPC2103	Half Bridge	80	6	5.5	6.5	2	1.3	29 39	0	760	460 630	8.7	23	195	150	BGA 6.05 x 2.3	EPC9039
EPC2029	Single	80	6	3.2	13	3.4	1.9	53	0	1410	820	17	48	360	150	BGA 4.6 x 2.6	EPC9046
EPC2105	Half Bridge	80	6	14.5 3.4	2.5 10	1 3.2	0.5 2	11 55	0	300 1100	200 800	3 12	9.5 38	75 320	150	BGA 6.05 x 2.3	EPC9041
EPC2021	Single	80	6	2.5	15	3.4	2.3	63	0	1650	970	20	90	420	150	LGA 6.05 x 2.3	EPC9034
EPC2038	Single with Gate Diode	100	6	3300	0.044	0.02	0.004	0.134	0	7	1.6	0.02	0.5	0.5	150	BGA 0.9 x 0.9	EPC9507
EPC2037	Single	100	6	550	0.115	0.032	0.025	0.6	0	14	6.5	0.1	1.7	2.4	150	BGA 0.9 x 0.9	EPC9051
EPC2107	Dual with Sync Boot	100	6	390 3300	0.19 0.044	0.077 0.02	0.041 0.004	0.9 1.25 0.134	0	16 7	17 1.6	0.3 0.02	1.7 0.5	3.8 0.5	150	BGA 1.35 x 1.35	EPC9063
EPC8010	Single	100	6	160	0.36	0.13	0.06	2.2	0	43	25	0.3	2.7	7.5	150	LGA 2.05 x 0.85	EPC9030
EPC2036	Single	100	6	73	0.7	0.17	0.14	3.9	0	75	50	0.7	1.7	18	150	BGA 0.9 x 0.9	EPC9050
EPC2106	Half Bridge	100	6	70	0.73	0.24	0.140	3.96 4.68	0	79	52 61	0.5	1.7	18	150	BGA 1.35 x 1.35	EPC9055
EPC2007C	Single	100	6	30	1.6	0.6	0.3	8.3	0	170	110	1.9	6	40	150	LGA 1.7 x 1.1	EPC9006C

eGaN FETs and ICs (continued)

Part Number	Configuration	V _{DS} max	V _{GS} max	Max R _{DS(on)} (mΩ) @ 5 V _{GS}	Q _G typ (nC)	Q _{GS} typ (nC)	Q _{GD} typ (nC)	Q _{OSS} typ (nC)	Q _{RR} (nC)	C _{ISS} (pF)	C _{OSS} (pF)	C _{RSS} (pF)	I _D (A)	Pulsed I _D (A)	Max T _J (°C)	Package (mm)	Development Board
EPC2016C	Single	100	6	16	3.4	1.1	0.55	16	0	360	210	3.2	18	75	150	LGA 2.1 x 1.6	EPC9010C
EPC2045	Single	100	6	7	5.2	1.7	1.1	21	0	570	260	5	16	130	150	BGA 2.5 x 1.5	EPC9078
EPC2001C	Single	100	6	7	7.5	2.4	1.2	31	0	770	430	10	36	150	150	LGA 4.1 x 1.6	EPC9002C
EPC2104	Half Bridge	100	6	6.3	7	2	1.2	35 47	0	800	450 600	7	23	165	150	BGA 6.05 x 2.3	EPC9040
EPC2032	Single	100	6	4	12	3	2	66	0	1270	800	12	48	340	150	BGA 4.6 x 2.6	EPC9062
EPC2022	Single	100	6	3.2	13.2	3.4	2.4	71	0	1400	840	7	90	390	150	LGA 6.05 x 2.3	EPC9035
EPC2110	Dual Common Source	120	6	60	0.8	0.25	0.19	4.9	0	80	50	0.75	3.4	20	150	BGA 1.35 x 1.35	n/a
EPC2033	Single	150	6	7	12	3.8	3.2	90	0	1160	480	6	48	260	150	BGA 4.6 x 2.6	EPC9047
EPC2012C	Single	200	6	100	1	0.3	0.2	10	0	100	64	0.4	5	22	150	LGA 1.7 x 0.9	EPC9004C
EPC2019	Single	200	6	50	1.8	0.6	0.35	18	0	200	110	0.7	8.5	42	150	LGA 2.77 x 0.95	EPC9014
EPC2010C	Single	200	6	25	3.7	1.3	0.7	40	0	380	240	1.8	22	90	150	LGA 3.6 x 1.6	EPC9003C
EPC2046	Single	200	6	25	2.9	1	0.6	22	0	285	145	1	11	55	150	BGA 2.77 x 0.95	EPC9079
EPC2047	Single	200	6	10	8.2	2.9	1.8	60	0	875	390	4	32	160	150	BGA 4.6 x 1.6	EPC9081
EPC2034	Single	200	6	10	8.8	3	1.8	75	0	950	450	2.3	48	200	150	BGA 4.6 x 2.6	EPC9048
EPC8002	Single	65	6	480	0.133	0.057	0.015	0.344	0	20	6.7	0.12	2	2	150	LGA 2.05 x 0.85	EPC9022

DrGaN^{PLUS}

Part Number	Description	V _{DS} (max)	I _D (max RMS)	Featured Product
EPC9201	PCB-based half-bridge circuit module	30	40	EPC2015C / EPC2023
EPC9203	PCB-based half-bridge circuit module	80	20	EPC2021

Half-Bridge Development Boards

Part Number	Description	V _{DS} (max)	I _D (max RMS)	Featured Product
EPC9036	Power Stage Evaluation of Monolithic GaN Half Bridge	30	25	EPC2100
EPC9018	Half Bridge Plus Driver for Low Duty Cycle Applications	30	35	EPC2015C EPC2023
EPC9031	Half Bridge Plus Driver	30	40	EPC2023
EPC9059	Half Bridge Parallel Evaluation For High Current Applications	30	50	EPC2100
EPC9066	Half Bridge Plus Driver with Synchronous Bootstrap	40	2.7	EPC8004
EPC9005C	Half Bridge Plus Driver	40	7	EPC2014C
EPC9001C	Half Bridge Plus Driver	40	15	EPC2015C
EPC9060	Half Bridge Plus Driver	40	25	EPC2030
EPC9032	Half Bridge Plus Driver	40	35	EPC2024
EPC9024	Half Bridge Plus Driver	40	4.4	EPC8004
EPC9049	Half Bridge Plus Driver	60	4	EPC2035
EPC9038	Power Stage Evaluation of Monolithic GaN Half Bridge	60	20	EPC2102
EPC9037	Power Stage Evaluation of Monolithic GaN Half Bridge	60	22	EPC2101
EPC9061	Half Bridge Plus Driver	60	24	EPC2031
EPC9033	Half Bridge Plus Driver	60	30	EPC2020
EPC9067	Half Bridge Plus Driver with Synchronous Bootstrap	65	2.7	EPC8009
EPC9022	Half Bridge Plus Driver	65	1.6	EPC8002
EPC9029	Half Bridge Plus Driver	65	3.5	EPC8009
EPC9057	Half Bridge Plus Driver	80	6	EPC2039
EPC9039	Power Stage Evaluation of Monolithic GaN Half Bridge	80	17	EPC2103
EPC9019	Half Bridge Plus Driver for Low Duty Cycle Applications	80	20	EPC2001 EPC2021
EPC9041	Power Stage Evaluation of Monolithic GaN Half Bridge	80	20	EPC2105
EPC9078	Half Bridge Plus Driver	80	20	EPC2045
EPC9046	Half Bridge Plus Driver	80	22	EPC2029
EPC9034	Half Bridge Plus Driver	80	27	EPC2021
EPC9080	Half Bridge Plus Driver for High Step Down / High Current	80	30	EPC2045 EPC2022
EPC9063	Half Bridge with Sync FET Bootstrap Gate Drive	100	1.5	EPC2107
EPC9050	Half Bridge Plus Driver	100	2.5	EPC2036
EPC9068	Half Bridge Plus Driver with Synchronous Bootstrap	100	2.7	EPC8010
EPC9055	Half Bridge Plus Driver	100	3	EPC2106
EPC9006C	Half Bridge Plus Driver	100	7	EPC2007C
EPC9010C	Half Bridge Plus Driver	100	7	EPC2016C
EPC9002C	Half Bridge Plus Driver	100	10	EPC2001C
EPC9040	Power Stage Evaluation of Monolithic GaN Half Bridge	100	15	EPC2104

Half-Bridge Development Boards (continued)

Part Number	Description	V _{DS} (max)	I _D (max RMS)	Featured Product
EPC9017	Half Bridge Plus Driver for Low Duty Cycle Applications	100	20	EPC2001C
EPC9062	Half Bridge Plus Driver	100	20	EPC2032
EPC9035	Half Bridge Plus Driver	100	25	EPC2022
EPC9030	Half Bridge Plus Driver	100	3.2	EPC8010
EPC9013	Multiple Half Bridges in Parallel	100	35	EPC2001C
EPC9047	Half Bridge Plus Driver	150	12	EPC2033
EPC9081	Half Bridge Plus Driver	160	15	EPC2047
EPC9048	Half Bridge Plus Driver	160	12	EPC2034
EPC9004C	Half Bridge Plus Driver	200	3	EPC2012C
EPC9014	Half Bridge Plus Driver	200	4	EPC2019
EPC9003C	Half Bridge Plus Driver	200	5	EPC2010C
EPC9079	Half Bridge Plus Driver	200	6	EPC2046

High Frequency Half-Bridge Development Boards

Part Number	Description	V _{DS} (max)	I _D (max RMS)	Featured Product
EPC9078	Half Bridge Plus Driver	30	15	EPC2111
EPC9024	Half Bridge Plus Driver	40	4.4	EPC8004
EPC9022	Half Bridge Plus Driver	65	1.6	EPC8002
EPC9029	Half Bridge Plus Driver	65	3.5	EPC8009
EPC9030	Half Bridge Plus Driver	100	3.2	EPC8010

Highly Resonant Wireless Power Evaluation Kits

Part Number	Description	Class	Output Power	Operating Frequency	Featured Product
EPC9111	High-Frequency, ZVS Class-D Wireless Power Evaluation Kit	3	35 W	6.78 MHz preset or user selectable	EPC2014C / EPC2038
EPC9112	High-Frequency, ZVS Class-D Wireless Power Evaluation Kit	3	50 W	6.78 MHz preset or user selectable	EPC2007C / EPC2038

AirFuel™ Alliance Compatible Wireless Power Evaluations Kits

Part Number	Description	Class	Output Power	Operating Frequency	Featured Product
EPC9127	AirFuel compatible, ZVS Class-D Wireless Power System	2	10 W	6.78 MHz	EPC2107 / EPC2036 EPC2019
EPC9128	AirFuel compatible, ZVS Class-D Wireless Power System	3	16 W	6.78 MHz	EPC2108 / EPC2036 EPC2019
EPC9120	AirFuel™ compatible, ZVS Class-D Wireless Power System	4	33W	6.78 MHz	EPC8010 / EPC2038 / EPC2019

Multi-Mode Wireless Power Evaluations Kit

Part Number	Description	Class	Output Power	Operating Frequency	Featured Product
EPC9121	AirFuel™ Compatible Qi/PMA Compatible	2 A6	10 W 5 W	6.78 MHz 6.165 KHz	EPC2107 / EPC2038 / EPC2036

Wireless Power Amplifier Boards

Part Number	Description	V _{IN}	V _{OUT}	I _{OUT}	Featured Product
EPC9051	AirFuel Class 2, 10 W Class E Amplifier	0 V - 40 V	V _{IN}	1 A	EPC2037
EPC9052	AirFuel Class 3, 16 W Class E Amplifier	0 V - 40 V	V _{IN}	1 A	EPC2012C
EPC9053	AirFuel Class 4, 33 W Class E Amplifier	0 V - 40 V	V _{IN}	1 A	EPC2019
EPC9083	AirFuel Class 5, 60 W Class E Amplifier	0 V - 80 V	V _{IN}	4 A	EPC2046
EPC9508	ZVS Class-D Wireless Power Amplifier	7 V - 36 V	V _{IN}	3 A	EPC8009 / EPC2007
EPC9506	ZVS Class-D Wireless Power Amplifier	8 V - 32 V	V _{IN}	10 A	EPC2014C / EPC2038
EPC9507	ZVS Class-D Wireless Power Amplifier	8 V - 36 V	V _{IN}	6 A	EPC2007C / EPC2038
EPC9509	AirFuel Class 3, 16 W ZVS Class D Amplifier	9 V - 24 V	52 V	1 A	EPC2108 / EPC2036
EPC9510	AirFuel Class 2, 10 W ZVS Class D Amplifier	9 V - 24 V	66 V	0.8 A	EPC2107 / EPC2036
EPC9512	AirFuel Class 4, 33 W ZVS Class D Amplifier	Mode Dependent	80 V	1.8 A	EPC8010 / EPC2038 / EPC2019
EPC9065	AirFuel Class 5, 60 W ZVS Class D Amplifier	12 V (max V _{DD})	80 V	1.8 A _{RMS}	EPC2007C / EPC8010
EPC9511	10 W Multi-Mode Wireless Power Amplifier	17 V - 24 V	66 V/26 V	1.7 A	EPC2107 / EPC2038 / EPC2036

Wireless Power Device Receive Boards

Part Number	Description	V _{IN}	V _{OUT}	Featured Product	Example Application
EPC9513	AirFuel Category 3, 5 W Device Receive Board	5	1 A	EPC2019	Smart Phone
EPC9515	AirFuel Category 4, 10 W Device Receive Board	5	2 A	EPC2019	Tablet, Phablet

DC-DC Conversion

Part Number	Description	V _{IN}	V _{OUT}	I _{OUT}	Featured Product
EPC9101	1 MHz Buck Converter	8 V - 19 V	1.2 V	18 A	EPC2014C / EPC2015C
EPC9107	Buck Converter	9 V - 28 V	3.3 V	15 A	EPC2016C
EPC9118	Buck Converter	30 V - 60 V	5 V	20 A	EPC2012C
EPC9115	500 W 1/8th Brick Converter	48 V - 60 V	12 V	42 A	EPC2020 / EPC2021

Class-D Audio

Part Number	Description	Output Power	Distortion/ Output Noise	Frequency Response	Featured Product
EPC9106	Class-D Audio Amplifier Evaluation Kit	150 W / 8 Ω	< 0.03% THD+N, > 107.8 dB	20 Hz - 20 kHz, ±0.5 dB	EPC2016C

LiDAR

Part Number	Description	V _{BUS (max)}	V _{INPUT (max)}	T _{pin (min)}	Featured Product
EPC9126	High Current Pulsed Laser Diode Driver Demo Board	80 V	5 V	6 ns	EPC2016C



For More Information

Please contact info@epc-co.com or your local sales representative

Visit our website: epc-co.com
Sign-up to receive EPC updates at

bit.ly/EPCupdates or text "EPC" to 22828



eGaN is a registered trademark of Efficient Power Conversion Corporation