


EPC2050 – Enhancement Mode Power Transistor

 V_{DS} , 350 V $R_{DS(on)}$, 80 mΩ max I_D , 6.3 A


Revised June 16, 2025

Gallium Nitride's exceptionally high electron mobility and low temperature coefficient allows very low $R_{DS(on)}$, while its lateral device structure and majority carrier diode provide exceptionally low Q_G and zero Q_{RR} . The end result is a device that can handle tasks where very high switching frequency, and low on-time are beneficial as well as those where on-state losses dominate.

APPLICATION NOTES:

- Easy-to-use and reliable gate, Gate Drive ON = 5 V typical, OFF = 0 V (negative voltage not needed)
- Top of FET is electrically connected to source

Questions:
Ask a GaN
Expert



Die Size: 1.95 x 1.95 mm

EPC2050 eGaN® FETs are supplied only in passivated die form with solder bumps

Applications

- High voltage DC-DC converter
- SMPS and UPS
- Solar power inverters and BMC
- Battery management systems
- DC-AC inverters
- Class D audio
- Lidar
- Medical imaging
- RF frequency switch
- Consumer and industrial wiring
- Multi-level AC-DC conversion
- EV charging
- Motor drives
- Wireless power Class-E amplifiers
- LED lighting

Benefits

- Ultra Small Footprint

Scan QR code or click link below for more information including reliability reports, device models, demo boards!



<https://l.ead.me/EPC2050>

Maximum Ratings			
PARAMETER		VALUE	UNIT
V_{DS}	Drain-to-Source Voltage (Continuous)	350	V
	Drain-to-Source Voltage (up to 10,000 5 ms pulses at 150°C)	420	
I_D	Continuous ($T_A = 25^\circ\text{C}$)	6.3	A
	Pulsed (25°C, $T_{PULSE} = 300 \mu\text{s}$)	26	
V_{GS}	Gate-to-Source Voltage	6	V
	Gate-to-Source Voltage	-4	
T_J	Operating Temperature	-40 to 150	°C
T_{STG}	Storage Temperature	-55 to 150	

Thermal Characteristics			
PARAMETER		TYP	UNIT
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case (Case TOP)	1.1	°C/W
$R_{\theta JB}$	Thermal Resistance, Junction-to-Board (Case BOTTOM)	10	
$R_{\theta JA_JEDEC}$	Thermal Resistance, Junction-to-Ambient (using JEDEC 51-2 PCB)	65	
$R_{\theta JA_EVB}$	Thermal Resistance, Junction-to-Ambient (using EPC99012 EVB)	45	

Static Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise stated)						
PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
BV_{DSS}	Drain-to-Source Voltage	$V_{GS} = 0 \text{ V}, I_D = 0.08 \text{ mA}$	350			V
I_{DSS}	Drain-Source Leakage	$V_{DS} = 280 \text{ V}, V_{GS} = 0 \text{ V}$		0.001	0.06	mA
I_{GSS}	Gate-to-Source Forward Leakage	$V_{GS} = 5 \text{ V}$		0.001	0.5	
	Gate-to-Source Forward Leakage [#]	$V_{GS} = 5 \text{ V}, T_J = 125^\circ\text{C}$		0.03	1	
	Gate-to-Source Reverse Leakage	$V_{GS} = -4 \text{ V}$		0.0005	0.1	
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 1 \text{ mA}$	0.7	1.3	2.5	V
$R_{DS(on)}$	Drain-Source On Resistance	$V_{GS} = 5 \text{ V}, I_D = 6 \text{ A}$		55	80	mΩ
V_{SD}	Source-Drain Forward Voltage [#]	$I_S = 0.5 \text{ A}, V_{GS} = 0 \text{ V}$		1.5		V

[#] Defined by design. Not subject to production test.

Dynamic Characteristics[#] ($T_J = 25^\circ\text{C}$ unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
C_{ISS}	Input Capacitance	$V_{GS} = 0\text{ V}, V_{DS} = 280\text{ V}$		423	628	pF
C_{RSS}	Reverse Transfer Capacitance			0.3		
C_{OSS}	Output Capacitance			81	122	
$C_{OSS(ER)}$	Effective Output Capacitance, Energy Related (Note 1)	$V_{GS} = 0\text{ V}, V_{DS} = 0\text{ to }280\text{ V}$		101		
$C_{OSS(TR)}$	Effective Output Capacitance, Time Related (Note 2)			125		
R_G	Gate Resistance			0.5		Ω
Q_G	Total Gate Charge	$V_{GS} = 5\text{ V}, V_{DS} = 280\text{ V}, I_D = 6\text{ A}$		2.9	4	nC
Q_{GS}	Gate-to-Source Charge	$V_{DS} = 280\text{ V}, I_D = 6\text{ A}$		1.3		
Q_{GD}	Gate-to-Drain Charge			0.3		
$Q_{G(TH)}$	Gate Charge at Threshold			0.9		
Q_{OSS}	Output Charge	$V_{GS} = 0\text{ V}, V_{DS} = 280\text{ V}$		35	53	
Q_{RR}	Source-Drain Recovery Charge			0		

[#] Defined by design. Not subject to production test.

All measurements were done with substrate connected to source.

Note 1: $C_{OSS(ER)}$ is a fixed capacitance that gives the same stored energy as C_{OSS} while V_{DS} is rising from 0 to 80% BV_{DSS} .

Note 2: $C_{OSS(TR)}$ is a fixed capacitance that gives the same charging time as C_{OSS} while V_{DS} is rising from 0 to 80% BV_{DSS} .


Figure 1: Typical Output Characteristics at 25°C 

Figure 2: Typical Transfer Characteristics




Figure 3: Typical $R_{DS(on)}$ vs. V_{GS} for Various Drain CurrentsFigure 4: Typical $R_{DS(on)}$ vs. V_{GS} for Various Temperatures

Figure 5a: Typical Capacitance (Linear Scale)




Figure 5b: Typical Capacitance (Log Scale)



Figure 6: Typical Output Charge and C_{OSS} Stored Energy

Figure 7: Typical Gate Charge




Figure 8: Typical Reverse Drain-Source Characteristics





Figure 9: Typical Normalized On-State Resistance vs. Temp.



Note: Negative gate drive voltage increases the reverse drain-source voltage.
EPC recommends 0 V for OFF.

All measurements were done with substrate shorted to source.

Figure 10: Typical Normalized Threshold Voltage vs. Temp.




Figure 11: Safe Operating Area







Figure 12: Typical Transient Thermal Response Curves



TAPE AND REEL CONFIGURATION

4 mm pitch, 8 mm wide tape on 7" reel




EPC2050 (Note 1)	Dimension (mm)		
	Target	MIN	MAX
a	8.00	7.90	8.30
b	1.75	1.65	1.85
c (Note 2)	3.50	3.45	3.55
d	4.00	3.90	4.10
e	4.00	3.90	4.10
f (Note 2)	2.00	1.95	2.05
g	1.50	1.50	1.60

Note 1: MSL 1 (moisture sensitivity level 1) classified according to IPC/ JEDEC industry standard.

Note 2: Pocket position is relative to the sprocket hole measured as true position of the pocket, not the pocket hole.


DIE MARKINGS



Part Number	Laser Markings		
	Part # Marking Line 1	Lot Date Code Marking Line 2	Lot Date Code Marking Line 3
EPC2050	2050	YYYY	ZZZZ

DIE OUTLINE

Solder Bar View




DIM	MICROMETERS		
	MIN	Nominal	MAX
A	1920	1950	1980
B	1920	1950	1980
c	400	400	400
d	800	800	800
e	180	200	220
f	360	375	390
g	160	175	190

Pad 1 is Gate;

Pads 2, 3, 4, 9, 10, 11, 12 are Source;


Pads 5, 6, 7, 8 are Drain

Side View



RECOMMENDED LAND PATTERN

(measurements in μm)




DIM	MICROMETERS
A	1950
B	1950
c	400
d	800
e	200
f	375
g	175

The land pattern is solder mask defined.

RECOMMENDED STENCIL DRAWING

(units in μm)



DIM	MICROMETERS
A	1950
B	1950
c	400
d	800
e	275
f	225
g	375
h	175

Recommended stencil should be 4 mil (100 μm) thick, must be laser cut, opening per drawing. The corner has a radius of R60.

Intended for use with SAC305 Type 4 solder, reference 88.5% metals content

Additional Resources Available

- Assembly resources available at: <https://epc-co.com/epc/design-support>
- Library of Altium footprints for production FETs and ICs: <https://epc-co.com/epc/documents/altium-files/EPC%20Altium%20Library.zip>
(for preliminary device Altium footprints, contact EPC)

Efficient Power Conversion Corporation (EPC) reserves the right to make changes without further notice to any products herein to improve reliability, function or design. EPC does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

eGaN® is a registered trademark of Efficient Power Conversion Corporation.
EPC Patent Listing: <https://epc-co.com/epc/about-epc/patents>

Information subject to change without notice.